

Super Nop Product Specifications

Face fibre	100% ASOTA®
Dye Method	Solution dyed Polypropylene fibres
Face weight	1750 gr/m ² (52 ounces per square yard)
Backing	Eco-DI-back® natural-synthetic composite rubber
Total weight	3200 gr/m ² (94 ounces per square yard)
Width	200 cm (6' 7")
Length	21 m (69")
Total Thickness	12.5 mm (0.5")

These products meet C.G.S.B. standards for Methenamine Pill-Test.
All ViFloor products meet ISO 9002 Certification.
Manufactured in the Netherlands

Vifloor
CANADA LTD
1-877-521-9014
www.vifloor.com

Super Series

Vifloor
CANADA LTD
1-877-521-9014

Needlepunch Maintenance Schedule for Commercial Installation

Proper Specification:

1. Carpet Colour - In heavy traffic areas such as entrances, a darker colour will retain its appearance longer.
2. Survey Your Facility and determine heavy, medium and light soil traffic areas and choose your carpet accordingly.
Heavy - Outside entrances, corridors, elevator lobbies, stairways and main aisles.
Medium - Secondary aisles, office spaces, meeting rooms and atriums.
Light - Back offices, conference rooms and executive areas.
3. Preventative Maintenance - For long term appearance, plan areas to trap soil before it reaches the carpet. Provide adequate walk-off matting at all building entrances. These should be used year round for wiping soil and water.

Routine Cleaning - Vacuuming

1. **Equipment** - Use a dual motor upright vacuum with a beater-bar or brushes with high suction. Low settings are acceptable due to the carpet being highly abrasion resistant.
2. **Method** - Slow deliberate vacuum-passes are more effective. A minimum of four passes, forward and back, are recommended for effective dirt removal.

3. Frequency

Carpet Area	Vacuumping
Heavy Traffic	→ Daily
Medium Traffic	→ Every other day
Light Traffic	→ Once or twice a week

Spots & Stains

1. Remove spills and stains immediately.
2. Solid substances should be removed first with a spoon.
3. Liquid spots can be dabbed with white blotting paper, repeat the dabbing until blotting paper is no longer wet.
4. If spot is still visible, use a carpet spot remover (use as little as possible) and dab spot simultaneously with wet cloth or sponge.
5. Never use commercial stain removers which could penetrate through the backing and damage the carpet.
6. Do not walk on the wet spot.
7. For more difficult stains, contact your sales representative. If possible, establish a "hot line" for employees to call for immediate response to spills. Spot cleaning should be done daily. The best time to identify stains is during regular vacuuming.

Deep Cleaning - Restoring

1. **Equipment** - Hot water extraction is the most effective method of removing deep soil. Units with heavy water pressure (PSI) and strong suction (water lift) are recommended for best results. Water temperature should not exceed 160°F.
2. **Method** - When extracting, do not "over wet" the carpet and extract as much water as possible with dry passes following the final wet pass. Avoid cleaning chemicals which leave residues. Remaining residue can attract soil and cause more frequent cleaning.
3. **Frequency**

Carpet Area	Hot Water Extraction
Heavy Traffic	→ Minimum four times per year
Medium Traffic	→ Minimum twice per year
Light Traffic	→ Once per year

Monitoring Your Carpet

Do a walk through inspection of all areas monthly. For optimum appearance and protection of your carpet, it may be necessary to adjust the frequencies of vacuuming, spot cleaning and extraction.

Commercial Grade Matting for Quality Buildings



PRODUCT CATALOGUE

Super Nop

CUSTOM INLAID LOGO WORK AVAILABLE

- ★ Logos are graphic inlaid and can be designed from graphic art, a business card or letter head
- ★ Logos are permanently incorporated into background colour
- ★ Logos enhance your matting installation and greet your visitors
- ★ Logos are a cost effective way to keep your image in front of your customers
- ★ Logos can be reproduced in any of the colours shown in this catalog



- | | |
|-------------------|----------------------|
| 1. 1120 Charcoal | 7. 1154 Loden |
| 2. 1175 Rainbow | 8. 1150 Green |
| 3. 1143 Dark Blue | 9. 1151 Hunter Green |
| 4. 1145 Mid Blue | 10. 1118 Taupe |
| 5. 1140 Blue | 11. 1155 Seagreen |
| 6. 1127 Dark Grey | |

FOR EXTRA HEAVY CONTRACT USE

- ★ Heavy duty needle punched matting product with hobnail pattern
- ★ Made with 100% Asota® solution dyed polypropylene fibers and can be installed indoors as well as outdoors
- ★ Spike and skate resistant and impervious to many chemicals such as caustic soda, chlorine, petroleum products, ice melters and salts
- ★ Use where heavy traffic demands extra durability in matting product
- ★ Permanently anti-static
- ★ Mold and mildew resistant and easily cleaned by vacuuming, hosing or hot water extraction
- ★ Holds approximately 7 litres of water per square yard
- ★ Arrows on backing indicate pile direction for installation
- ★ Passes C.G.S.B. Standards for flammability (Pill Test)



- | | |
|--------------------|------------------|
| 12. 1161 Rosewood | 17. 1130 Red |
| 13. 1110 Chocolate | 18. 1116 Savanne |
| 14. 1152 Autumn | 19. 1105 Natural |
| 15. 1160 Garnet | 20. 1115 Beige |
| 16. 1135 Burgundy | 21. 1106 Desert |